



AUDIO VISUAL & SIGNALLING



PRODUCT CATALOGUE



TOWER LAMPS



- 1) LED based (5 colours - red,amber,green,blue,white)
- 2) Slick, contemporary design.
- 3) Excellent luminosity.
- 4) Available in Steady, Flasher, Buzzer Modes.
- 5) From single tier upto six tier (one colour will repeat itself)
- 6) Operating Voltages available: 24 VAC/DC, 110 VAC/DC, 230 VAC
- 7) 3 way Mounting
- 8) Standard grey body, but can be provided with White or Black body also.
- 9) Lens can be coloured or transparent.
- 10) **Single Tower Multicolor (4 Colour. : R.Y.G.B.) also available.**



CNC LED LAMP

LAMP (WATTAGE)	OPERATING VOLTAGE	DIMENSIONS (mm) Glass Ø M-60
AE-CNC-5W	24VDC/ 230VAC	325
AE-CNC-8W	24VDC/ 230VAC	360
AE-CNC-14W	24VDC/230VAC	485
AE-CNC-20W	24VDC/ 230VAC	735

- 1) Cable- 2mtr.
- 2) Protection Class - IP67 Tested by NABL accredited Lab.
- 3) LED- Osram / Edison
- 4) LED Driver : Inbuilt
- 5) Enclosure : Moulded side bracket with rotating glass
- 6) Colour : LED - Cool White / Warm White
- 7) 12VDC, 24VAC & 110VAC Operating Voltage available on Request
- 8) Glass Length can be customized for Quantity Order.

SPOT LIGHT

Product Code : AE-LSL - < Voltage >

Goose-Neck Pipe of 18 Inch Length for Better Reach and Angles

Operating Voltage : 24VAC / 24VDC / 230VAC

Power Consumption : 6W

Dimensions (mm) : Mounting Box - 100 X 100 X 75 (H)

Mounting : Clamp / Bracket for Mounting

Length : 12 Inches, 24 Inches on Request

Spot Light with Magnetic Base also available.



LED ARM (SPOT) LIGHT / ARM LIGHT

LED Based Arm Spot Light / Arm Light for Machines & Work Station 30 Inch Arm Length for Better Reach

Product Code : AE-LASL - < Voltage >

Product Code : AE-LAL - < Voltage >

Operating Voltage : AE-LASL 24VAC / 24VDC / 230VAC

: AE-LAL 24VDC / 230VAC

Power Consumption : AE-LASL 6W

: AE-LAL 8W / 14W

Dimensions (mm) : AE-LASL Mounting Box - 100 X 100 X 75 (H)

: AE-LAL Mounting Box - 100 X 100 X 75 (H)

Mounting : Clamp / Bracket for Mounting



PHASER (LED)

Bus Bar Indicator / DSL Indicator (LED)

Product Code : AE-PHASER - < Voltage >

Available Input Voltage : 230 VAC, 110 VAC, 48 VAC

(415 VAC Also available)

: Fuse- based protection for each indicator

Color : Red, Amber, Blue (LED)

Dimensions (mm) : 395 x 100 x 145 (H)

Mounting : Side Mounting Flanges (4 Mounting Holes of M6 Dia.)



Electronic Hooter

Electronic Hooter - Intermittent

Product Code : AE-H - < Voltage >

Operating Voltage : 230VAC, 110 VAC, 48 VAC/DC, 24 VAC/DC, 12 VAC/DC

Dimensions (mm) : 96 X 96 X 110 (Cut - Out 92 x 92)

Mounting : Panel Mounting or Base Mounting (Clamp Type)

Sound : 98-102 dB (at 1 meter, under test condition)

Universal Voltage : 24 VAC/DC To 240 VAC/DC

Dimensions (mm) : 96 x 96 x 90



Electronic Hooter + Flasher / Revolving

Product Code : AE-HF - < Colour > - < Voltage >

Lumination : Red, Amber, Blue, Green

Operating Voltage : 24 VDC, 110 VAC, 230 VAC

Dimensions (mm) : 200 X 145 X 110

Mounting : Panel Mounting Type with 'C' Clamp (M5 Screws)

Sound : 98-102 dB (at 1 meter, under test condition)



LED PANEL LIGHT

LED T8 Panel Lights

Product Code : AE-LPL - < Voltage >

Lumination : Normal White

Operating Voltage : 230 VAC, 110 VAC, 24 VDC, 12 VDC

Power Consumption : @ 5w

Dimensions : 1 ft (Length)

Mounting : On 2 Clamps (clamps provided)



Mfg. By :

Antariksh Enterprises
M.I.D.C. Satpur, Nashik. (MH)



Mktd. By :

NASA ENTERPRISES
Let's grow together...

66, 2nd Floor, Plot C10/1, Nice Indl. Estate, A Road, MIDC, Satpur,
Nashik - 422007 Tel.no. : 0253-2357729 Email: info@nasaent.co.in

Authorised Channel Partner

Disclaimer : Please ensure suitability of products for your specific application before ordering. Due to continuous development, the details are subject to change without notice, and the images depicted herein are only for reference. Actual product may differ in appearance / function.